



RUBBEDIN PTY LTD
MATERIAL SAFETY DATA SHEET

Not classified as hazardous according to criteria of Worksafe Australia

PRODUCT: STOVE POLISH

SECTION 1 – PRODUCT IDENTIFICATION

Product Name: STOVE POLISH
Manufacturers Code: 03

Distributor: Rubbedin Pty Ltd
Emergency Phone No: 0405358685
Regular Phone No: (07) 3245 3255
Fax: (07) 3245 2554
Email: rubbedin@rubbedin.com.au
Address: Unit 1/43 Neumann Road
Capalaba QLD 4157

SECTION 2 – HAZARDS IDENTIFICATION

Classification: This material is not classified as hazardous according to criteria of NOHSC.

UN No:	Not applicable	PACKAGING GROUP:	Not applicable
CLASS:	Not applicable	HAZCHEM:	Not applicable
SUB-RISK	Not applicable	POISONS SCHEDULE:	Not applicable

SECTION 3 – INGREDIENTS

MATERIAL/COMPONENT	Wt%	CAS NUMBER
Products not classified as hazardous	to 100%	

SECTION 4 -EMERGENCY AND FIRST AID PROCEDURES

For advice, contact a Poisons Information Centre (Phone e.g. Australia 131 126; New Zealand 0 800 764766) or a doctor.

EMERGENCY AND FIRST AID PROCEDURES

Ingestion: Do not induce vomiting. Rinse mouth with water and give plenty of water to drink. If vomiting occurs give further water. Seek immediate medical assistance.
Eye contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Seek medical assistance.
Skin contact: Wash contaminated skin with plenty of water. Remove contaminated clothing and wash before re-use. If irritation occurs seek medical advice.
Inhalation: Unlikely due to physical form of product. Remove victim from exposure. Seek medical advice if effects persist.
Notes to physician: Treat symptomatically.

SECTION 5 – FIRE AND EXPLOSION DATA

Flash Point:	Non-flammable	Method:	Not applicable
Flammability Limits in Air (% Volume)			
Lower:	Not applicable	Upper:	Not applicable

Fire Extinguishing Media: Not combustible, however, if material is involved in a fire use: Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).



RUBBEDIN PTY LTD

MATERIAL SAFETY DATA SHEET

Special Fire Fighting Procedures: Not combustible, however, if material is involved in a fire, fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to products of decomposition.

Unusual Fire and Explosion Hazards:

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill or Leak: Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination. Contain - prevent material entering drains and waterways. Use absorbent (soil, sand, or other inert material). Collect and seal in properly labelled drums for disposal. If contamination of sewers or waterways has occurred advise the local emergency services.

Disposal: Dispose of according to Local Authority Regulations.

SECTION 7 HANDLING AND STORAGE

Handling & Storage: Store in a cool, dry, well ventilated place away from direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed at all times - check regularly for leaks. Avoid generating dusts.

Other:

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits: No value assigned for this specific material by the National Occupational Health and Safety Commission (Worksafe Australia).

Engineering measures: Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use. Avoid generating dusts.

Personal protection: Avoid skin and eye contact. Wear overalls, safety glasses and impervious gloves. If inhalation risk exists or dust is being generated from usage, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (C):	Not determined	Volatiles:	>80%
Melting Point(C):	Not determined	Press@20C mm Hg:	Not available
Specific Gravity:	1.25 – 1.35	VAP Density:	Not available
Sol In Water (g/l):	Soluble	pH:	9.0 – 10.0
Appearance:	Black cream		
Evaporation Rate (nButyl Acetate=1)	Not applicable		

SECTION 10 – STABILITY AND REACTIVITY DATA

Stability	Stable under normal temperature and pressure
Conditions to Avoid	Oxidising agents, extremes in temperature.
Incompatibilities	Oxidising agents, strong acids, strong alkalis.
Hazardous decomposition products:	Toxic fumes of carbon oxides on combustion or oxidation.
Hazardous Polymerisation:	Will not occur



RUBBEDIN PTY LTD

MATERIAL SAFETY DATA SHEET

SECTION 11 - TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

HEALTH EFFECTS

- Eyes: Contact with eyes may cause irritation. Dust generated while using this product contains abrasive material which can cause irritation of the eyes.
- Skin: Contact with skin can cause irritation, (minor itching, burning, and/or redness) dermatitis.
- Inhalation: Unlikely due to the physical form of the product. Shaking the dried product from cloths etc may produce dust which will contain kaolin. Inhalation of this dust may cause difficulty in breathing. It can cause coughing, wheezing and possible long term damage to the lungs.
- Ingestion: Ingestion can cause possible gastrointestinal irritation, nausea, vomiting, and diaorrhea.

Long Term Effects:

No information available for the product.

Toxicological Data:

No LD50 data available for the product.

SECTION 12 - ECOLOGICAL INFORMATION

Avoid contaminating waterways

SECTION 13 - DISPOSAL CONSIDERATIONS

Dispose of material according to Local Authority Regulations or through a licensed waste contractor.

SECTION 14 TRANSPORT INFORMATION

- Road and Rail Transport: Not currently classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.
- Marine Transport: Not currently classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.
- Air Transport: Not currently classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

SECTION 15 REGULATORY INFORMATION

Classification: This material is not classified as hazardous according to criteria of NOHSC. All the constituents of this material are listed on the Australian Inventory of Chemical Substances.

Poison Schedule: Not applicable

SECTION 16 OTHER INFORMATION

CONTACT POINTS

ORGANISATION	TELEPHONE	ASK FOR
Poisons Information Centre – Australia Wide	131126	
Rubbedin Pty Ltd:		
Technical Manager:	(07) 3245 3255	
Emergency Co-ordinator:	0405358685	
Fire Brigade	000	Fire Brigade
Police	000	Police

The MSDS is valid for five years from date of issue but may be withdrawn and revised at any time prior to that date.



RUBBEDIN PTY LTD
MATERIAL SAFETY DATA SHEET

All information contained in the Data Sheet is as accurate as possible at the time of issue. It is meant to describe the safety requirements of our products and should not be construed as guaranteeing specific properties. As per the Worksafe Guidance Note NOHSC 3017, each user should review the information in the specific context of the intended application. No expressed or implied warranties nor any responsibility for damages resulting from use of the information are given other than those implied mandatory by Commonwealth, State or Territory Legislation. If this product is to be re-packaged by others, it will be necessary for a new MSDS to be generated by the re-packer.

PREPARED BY: Malcolm Swanney BSc CHEM

Title: Chemist

Date: 15/08/06